



## Whitemountain - Part of the Breedon Group

5 Blackwater Road, Mallusk, Co. Antrim, BT36 4TZ. Tel: + 44 (0) 28 9250 1000 www.whitemountain.co.uk

<b>Date CE mark affixed</b>	<b>19</b>
<b>Conforms to EN 771-3: 2011</b> <b>Category I - Aggregate Concrete Masonry Units</b> <b>440mm x 100mm x 215mm</b> <b>Product Code: B016 - 5.2N Lightweight Block</b>	
<b>Dimensions:</b> 440mm x 100mm x 215mm	
<b>Dimensional Tolerances:</b>	Category: D1 Flatness: NPD Plane Parallelism: NPD
<b>Configuration:</b>	Group 1 unit to EN 1996-1-1
<b>Compressive Strength:</b>	Declared Mean: $\geq 5.2 \text{ N/mm}^2$ [ $\perp$ bed face]
<b>Dimensional Stability:</b>	Moisture Movement: $\leq 0.3 \text{ mm/m}$
<b>Shear Bond Strength:</b>	Declared Value: $0.15 \text{ N/mm}^2$
<b>Reaction to Fire:</b>	Euroclass A1
<b>Water Absorption:</b>	Declared Value: $\leq 5 \text{ g/m}^2\text{s}$
<b>Water Vapour Diffusion Coefficient:</b>	Declared Value: 5/15
<b>Direct Airborne Sound Insulation:</b>	Gross Dry Density: $1250 \text{ kg/m}^3$ Configuration: As above
<b>Thermal Conductivity:</b>	Declared Value: $0.36 \text{ W/mK}$ ( $\lambda_{10, \text{dry, unit}} \text{ S1}$ )
<b>Dangerous Substances:</b>	See Note
<b>Note: Information on Dangerous Substances will only be given when and where required in the appropriate form. See Annex ZA3 of BS EN 771-3:2011</b>	

## DECLARATION OF PERFORMANCE

1. Product Type: **5.2N Lightweight Pumice Block**
2. Identification: **Product code and type is shown on delivery ticket**
3. Intended Use: **Internal & External Walls, Columns, and Partitions**
4. Manufacturer: **Whitemountain, 5 Blackwater Rd, Mallusk, Co. Antrim, BT36 4TZ.**
5. Authorised Representative: **Not applicable**
6. AVCP: **System 2+**
7. FPC & Initial Type Testing: **The initial type testing and the factory production control of the product identified in 1. have been successfully implemented by the manufacturer identified in 4.**
8. ETA: **Not applicable**
9. Declared Performance:

Essential Characteristics	Performance	Harmonised Standard
<b>Dimensions:</b>	440mm x 100mm x 215mm	EN 771-3 : 2011
<b>Dimensional Tolerances:</b>	Category: D1 Flatness: NPD Plane Parallelism: NPD	
<b>Configuration:</b>	Group 1 unit to EN 1996-1-1	
<b>Compressive Strength:</b>	Declared Mean: $\geq 5.2 \text{ N/mm}^2$ [ $\perp$ bed face]	
<b>Dimensional Stability:</b>	Moisture Movement: $\leq 0.3 \text{ mm/m}$	
<b>Shear Bond Strength:</b>	Declared Value: $0.15 \text{ N/mm}^2$	
<b>Reaction to Fire:</b>	Euroclass A1	
<b>Water Absorption:</b>	Declared Value: $\leq 5 \text{ g/m}^2\text{s}$	
<b>Water Vapour Diffusion Coefficient:</b>	Declared Value: 5/15	
<b>Direct Airborne Sound Insulation:</b>	Gross Dry Density: $1250 \text{ kg/m}^3$ Configuration: As above	
<b>Thermal Conductivity:</b>	Declared Value: $0.36 \text{ W/mK}$ ( $\lambda_{10, \text{dry, unit}} \text{ S1}$ )	
<b>Dangerous Substances:</b>	See Note	

**Note: Information on Dangerous Substances will only be given when and where required in the appropriate form. See Annex ZA3 of BS EN 771-3:2011**

**10.** The performance of the product identified in **1.** is in conformity with the declared performance in **9.**

*This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in **4.***

Signed on behalf of the manufacturer by:



Alan Donaghy (Technical Manager)