




Whitemountain - Part of the Breedon Group

5 Blackwater Road, Mallusk, Co. Antrim, BT36 4TZ. Tel: + 44 (0) 28 9250 1000 www.whitemountain.co.uk

| | |
|---|---|
| Date CE mark affixed | 19 |
| Conforms to EN 771-3: 2011 Category I - Aggregate Concrete Masonry Units 440mm x 100mm x 215mm Product Code: B018 - 7.3N Lightweight Block | |
| Dimensions: 440mm x 100mm x 215mm | |
| Dimensional Tolerances: | Category: D1 Flatness: NPD Plane Parallelism: NPD |
| Configuration: | Group 1 unit to EN 1996-1-1 |
| Compressive Strength: | Declared Mean: $\geq 7.3 \text{ N/mm}^2$ [\perp bed face] |
| Dimensional Stability: | Moisture Movement: $\leq 0.3 \text{ mm/m}$ |
| Shear Bond Strength: | Declared Value: 0.15 N/mm^2 |
| Reaction to Fire: | Euroclass A1 |
| Water Absorption: | Declared Value: $\leq 5 \text{ g/m}^2\text{s}$ |
| Water Vapour Diffusion Coefficient: | Declared Value: 5/15 |
| Direct Airborne Sound Insulation: | Gross Dry Density: 1250 kg/m^3 Configuration: As above |
| Thermal Conductivity: | Declared Value: 0.36 W/mK ($\lambda_{10, \text{dry, unit}} \text{ S1}$) |
| Dangerous Substances: | See Note |
| Note: Information on Dangerous Substances will only be given when and where required in the appropriate form. See Annex ZA3 of BS EN 771-3:2011 | |

DECLARATION OF PERFORMANCE

1. Product Type: **7.3N Lightweight Pumice Block**
2. Identification: **Product code and type is shown on delivery ticket**
3. Intended Use: **Internal & External Walls, Columns, and Partitions**
4. Manufacturer: **Whitemountain, 5 Blackwater Rd, Mallusk, Co. Antrim, BT36 4TZ.**
5. Authorised Representative: **Not applicable**
6. AVCP: **System 2+**
7. FPC & Initial Type Testing: **The initial type testing and the factory production control of the product identified in 1. have been successfully implemented by the manufacturer identified in 4.**
8. ETA: **Not applicable**
9. Declared Performance:

| Essential Characteristics | Performance | Harmonised Standard |
|--|---|---------------------|
| Dimensions: | 440mm x 100mm x 215mm | EN 771-3 : 2011 |
| Dimensional Tolerances: | Category: D1 Flatness: NPD Plane Parallelism: NPD | |
| Configuration: | Group 1 unit to EN 1996-1-1 | |
| Compressive Strength: | Declared Mean: $\geq 7.3 \text{ N/mm}^2$ [\perp bed face] | |
| Dimensional Stability: | Moisture Movement: $\leq 0.3 \text{ mm/m}$ | |
| Shear Bond Strength: | Declared Value: 0.15 N/mm^2 | |
| Reaction to Fire: | Euroclass A1 | |
| Water Absorption: | Declared Value: $\leq 5 \text{ g/m}^2\text{s}$ | |
| Water Vapour Diffusion Coefficient: | Declared Value: 5/15 | |
| Direct Airborne Sound Insulation: | Gross Dry Density: 1250 kg/m^3 Configuration: As above | |
| Thermal Conductivity: | Declared Value: 0.36 W/mK ($\lambda_{10, \text{dry, unit}} \text{ S1}$) | |
| Dangerous Substances: | See Note | |
| Note: Information on Dangerous Substances will only be given when and where required in the appropriate form. See Annex ZA3 of BS EN 771-3:2011 | | |
| <p>10. The performance of the product identified in 1. is in conformity with the declared performance in 9.</p> <p style="text-align: center;"><i>This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in 4.</i></p> | | |
| Signed on behalf of the manufacturer by: |  Alan Donaghy (Technical Manager) | |